

**emlite's range of modular meters serve as the perfect base for ASL Holding's ASLH382 module. The module enables automatic meter reading of micro-generation or other similar sites via the GSM network**

### Features -

#### Meter

- Fully MID approved
- Measures Import and Export, Active and Reactive Energy
- Power Quality Information - Volts, Current, Power etc.
- GSM Signal Strength Display

#### Communication module

- Optimised Internal Antenna
- Simple SIM card Fitting
- External Antenna option, where required
- Simple installation to meter without need for de-energising mains supply

The emlite modular meter range allows a range of communication modules to be fitted. Designed specifically for the collection of micro-generation metering and feed-in tariff data, the ASLH382 module provides remote collection of meter readings especially generation metering of wind, solar and any other renewable energy installations, through the mobile phone network's GPRS service.

The meter is a fully MID approved device and can provide functionality over and above that required for generation metering making it suitable for many other applications. Additional functionality includes Time-of-Use Rate Switching, Power Quality Recording, Active (kWh) and Reactive (kvarh) energy measurement across both import and export. The module is capable of accessing and configuring these additional features remotely.

The overall solution has been designed to minimise installation time and reduce the need for return site maintenance visits. An indication of the GSM signal strength is provided on the meter display together with the GSM network operator. This single display allows the installer to leave site confident that the installation is fully operational with a robust communication link.



## Communication Module

The communications module simply installs to the top of the meter using the meter's metering data port and mains supply connectors. Installation of the module to the meter can be made at the time of installation or supplied ready assembled directly from the factory thus saving time and effort on site.

The module is fitted with an optimised internal antenna designed to reduce the need for external antennas, even in low signal strength areas. Utilising the GPRS service, a variety of metering data is available including the half hourly profiling of import and export energy for the previous 120 days.

Standard or Solid State (Chip) SIMs may be fitted. In the case of standard SIMs, installation is simple via a holder fitted to the underside of the module. A simple Push-Push action inserts and removes the SIM.

emlite and its partner ASL Holdings are able to offer a selection of data collection services and airtime packages including network resilient SIMs which allow automatic network switching in cases of poor primary network coverage, removing the need to swap SIM cards in the field.



**Simple SIM card installation**

## Technical Data - Meter Part Number EMA1.az

<b>Electrical</b>	Voltage	Nominal voltage	220V—240V
		Maximum	276V
		Voltage withstand	415V continuously
	Frequency	Nominal frequency	50Hz
		Frequency variation	± 5%
	Current	Basic current (Iref)	5, 10, 15 or 20A
<b>Metrology</b>	Accuracy	Maximum (Imax)	100A
		Active energy	Class B, to EN 50470 1-3

Meets the essential requirements of the Measuring Instruments Directive (MID) 2004/22/EC. MID (Module B) Certificate Number 0120/SGS0083.

<b>Environmental</b>	Temperature Range	-25°C to +55°C
	Ingress protection	IP52, to BS EN 60529

Meters are intended for installation in a in a class E2 electromagnetic environment and Class M1 Mechanical Environment according to 2004/22/EC Directive

<b>Physical</b>	Terminal arrangement	BS 7856
	Main Terminal size	8.2 mm diameter
	Terminal Construction	Solid brass

<b>Dimensions</b>	(including module)	182H×126W×68D
-------------------	--------------------	---------------



**emlite Ltd, 10 Reynolds Business Park, Stevern Way, Peterborough PE1 5EL**  
**www.em-lite.co.uk**

**tel: +44 (0)1733 890060      email: sales@em-lite.co.uk**